(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 1 September 2005 (01.09.2005)

PCT

(10) International Publication Number WO 2005/079949 A1

(51) International Patent Classification7:

B01D 35/30

(21) International Application Number:

PCT/US2005/005062

- (22) International Filing Date: 17 February 2005 (17.02.2005)
- (25) Filing Language:

English

(26) Publication Language:

English


(30) Priority Data: 60/545,030

17 February 2004 (17.02.2004)

- (71) Applicant (for all designated States except US): STANA-DYNE CORPORATION [US/US]; 92 Deerfield Road, Windsor, Connecticut 06095 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): JANIK, Leon, P. [US/US]; 879 North Street, Suffield, Connecticut 06078 (US). VARDION, Stephen, J. [US/US]; 81 Rolling Hills Drive, Glastonbury, Connecticut 06033 (US). TORNATORE, Thomas, M. [US/US]; 162 Brainard

Connecticut 06795 (US). WILLIAMS, Michael, J. [US/US]; 144 Hampshire Drive, Glastonbury, Connecticut 06033 (US).

- (74) Agent: ALIX, YALE & RISTAS, LLP; 750 Main Street, 14th Floor, Hartford, Connecticut 06103 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),



the nut (70) at its periphery corners and includes structures that prevent rotation of the nut relative to the insert body (20). Retaining arms (24) project upwardly from the insert body (20) and are bent over the nut (70) to axially retain the nut (70) seated against the ledges. The insert body (20) and the nut (70) are inexpensively formed in separate automated operations. Assembly of the nut (70) into the insert body (20) may also be automated.



WO 2005/079949 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CO, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.